

Polluted Soil Remediation of Heavy Chlorinated Solvents in Saturated Porous Media: Effects of Thermal and Chemical Enhancements

Stéfan Colombano (s.colombano@brgm.fr), Hossein Davarzani, Ioannis Ignatiadis, Jacques Deparis, Dominique Guyonnet (BRGM – French Geological Survey)
Eric D. van Hullebusch (IHE Delft)
David Huguenot (Université Paris-Est)

Background/Objectives.

Recovery of chlorinated solvents (CSs) as a free product generally relies on pumping and pumping/skimming. However, this technique is time consuming and does not allow major recovery of CSs as free product and associated dissolved emissions. Our study focuses on the beneficial effects of thermal and chemical enhancements for recovering free product composed of heavy chlorinated compounds (hexachlorobutadiene, hexachloroethane, perchloroethylene, pentachlorobenzene, trichloroethylene, etc.).

Approach/Activities.

In this study, the rheological parameters of the dense non-aqueous phase liquid (DNAPL) were characterized: i.e., density, dynamic viscosity, interfacial tension (water/DNAPL) and contact angles (water/DNAPL). First, the imbibition-drainage tests were conducted in a small cell to determine the capillary pressure-saturation functions. Then, tests were performed in a column (1D tests) in order to validate the numerical model. Finally, pumping tests at different flow rates were carried out in a tank (2-D tests), in order to optimize the processes. These tests were carried out using glass beads of different diameters (0.1 to 1 mm) at different temperatures (10 and 45 °C) and with the application of different surfactants (SDBS, Triton X-100, Aerosol MA-80, and Tween 80). DNAPL flow was monitored using time domain reflectometry (TDR) probes, geophysical probes (induced polarization) as well as an imaging technique (Light Reflected Method-LRM).

Numerical models were developed using COMSOL Multiphysics® for 1-D and 2-D cases and the experimental data were compared with simulations results.

Results/Lessons Learned.

The results show that increasing the temperature from 10 to 45°C decreases the dynamic viscosity of DNAPLs (respectively, from 5.5 ± 0.20 to 2.8 ± 0.08 mPa.s) and has a limited influence on the interfacial tension (12 mN/m) and the contact angles (70°). The surfactants were found to reduce the interfacial tensions from 12 mN/m to 1 mN/m, depending on surfactant nature and concentration.

Retention curves of the two-phase system (capillary pressure as a function of water saturation) obtained using small cells were compared to various analytical models. The best correlations were obtained with the van Genuchten - Mualem model and the Brutsaert - Burdine model. These retention curves show that: (i) residual DNAPL saturation decreases by 30% when temperature increases from 10 to 45°C; (ii) surfactant addition globally decreases the irreducible saturation of water by 25% (i.e., the surfactants can, at constant pressure, increase the mobility of DNAPLs) and; (iii) aerosol MA-80 decreases the residual saturation by 24%.

The pumping experiments in 2-D tanks allows (using geophysical and image interpretation) estimating the radius of influence (ROI) as well as the optimal pumping flow rate (PFR). The ROI of pumping increases significantly with the thermal and chemical enhancements (e.g., twice larger

using surfactants). On the other hand, at higher PFRs, the beneficial effect of enhancement is less significant.

Finally, the developed numerical models of two-phase flow in porous media accurately reproduce the experiments data. In particular, the model can predict the displacement of the water-DNAPL interface.