

---

# LONG-TERM SOIL VAPOR EXTRACTION MONITORING AND EFFECTIVENESS IN TWO ADJOINING LOW PERMEABILITY ZONES


CONFERENCE ON REMEDIATION OF CHLORINATED AND RECALCITRANT COMPOUNDS

ROBERT W. PLYBON, P.E.  
PALM SPRINGS, CA  
11 APRIL 2018




# INTRODUCTION

- SLAC = SLAC National Accelerator Laboratory
  - A U.S. Department of Energy (DOE) laboratory operated by Stanford University
- FHWSA = Former Hazardous Waste Storage Area



# FHWSA HISTORY

- Used for storage of hazardous materials from late 1960s to early 1980s
- VOCs found in both groundwater and soil vapor
- Dual-Phase Extraction (DPE) has been primary element of remedy at FHWSA since 2006.



# FHWSA CURRENT USE



Google Earth

Aerial photograph provided by Google Earth



---

## LOW PERMEABILITY SOIL

- Ladera and Santa Clara Formations covered by thin clay/import fill
  - Micro-fractured silty-sandstone, behaves as low permeability media
  - Intrinsic permeability  $\sim 10^{-9}$  cm<sup>2</sup>
  - Saturated hydraulic conductivity  $\sim 10^{-5}$  -  $10^{-4}$  cm/s
- Soil vapor monitoring was implemented to:
  - Determine risk-based area of concern (for remediation)
  - Monitor remediation progress

# SOIL VAPOR PROBES

- Designed for sampling in low permeability soil
  - Installed with long sand filter pack
  - Minimum 4-liter pore space in sand pack, guaranteeing 1-liter sample
- 56 soil vapor probes (SVPs) installed between 2003 to 2016




Diagram not to scale

Diagram modified from ERI Inc. Draft Technical Memorandum dated 23 June 2010

---

# SVP SAMPLING METHODOLOGY

- Equilibration method – designed for low permeability
  - Fixed probes are long term, allowing VOC concentration in sand pack void space to equilibrate with soil gas before sampling
  - Purging limited to 3x tubing volume (not sand pack volume), ~50 mL
- 1-liter sample collected (summa canister)
  - 1 liter = ~25% of sand pack void space (4 liters)
  - Vacuum during sampling does not exceed 100 in-WC limit, even if no soil gas flows from soil into sand pack during sample collection
- Has provided representative results (over 14 years of monitoring), key to risk assessment and remediation monitoring

# SVP MONITORING AND RISK SCORE CALCULATION

- Analytical results for VOCs in each SVP sample used to calculate cumulative “risk scores”
- Calculated using risk-based Human Health Preliminary Remediation Goals (HH-PRGs) based on vapor intrusion pathway for unrestricted future land use
- Risk score of 1 = cancer risk of  $1 \times 10^{-6}$
- Plotted for ‘spatial risk characterization’
- Risk scores are primary method of evaluating risk and remediation effectiveness



Maximum Soil Vapor Risk, pre-2006






# DPE PILOT TEST AND INTERIM DPE SUCCESSFUL

- 2003: DPE Pilot Test
  - SVE shown to be potentially feasible (low air flow attainable)
- 2004-2005: Interim DPE
  - >99% risk reductions shown at SVP-1 and SVP-2



# FULL SCALE DPE IMPLEMENTED




- 2006: Full scale DPE system began operation
  - 23 DPE wells
  - Total SVE flow rate between 50 to 90 scfm
- 15 SVPs to monitor progress
  - filter packs 5 – 8 feet bgs



# DPE HAS PARTIAL SUCCESS

- 2011: Risk-based AOC reduced by 85%
- Successful for most SVPs
  - 1-year rebound test in 2012 proves sustainability of risk score reductions
- Still ineffective in some SVPs

Soil Vapor Risk, 2011



## NEW SVPs INSTALLED TO INVESTIGATE SITE MODEL

- Focused on thin shallow clay above Santa Clara Formation and Ladera Sandstone
- 2014: SVP-29 and SVP-30 installed

SVP	Filter Pack Interval (feet)	Risk Score (May 2015)
SVP-6	5 – 8.9	200
SVP-29	3.0 – 4.2	900
SVP-30	11.0 – 14.0	0.02




---



# EXPANDED CHARACTERIZATION OF SHALLOW SOIL

- Most existing SVPs below thin clay layer (Lower Soil Unit)
- Some existing SVPs partially within thin clay layer (Upper Soil Unit)
- Between 2014 and 2016, added 26 new SVPs within Upper Soil Unit

# HIGH RESOLUTION CROSS SECTIONS DEVELOPED



# SVPs IN LOWER SOIL UNIT & UPPER SOIL UNIT



# ALTERNATIVE REMEDY FOR UPPER SOIL UNIT

- Soil vapor monitoring indicated SVE was not effective in Upper Soil Unit and delineated the area of concern
- Performed evaluation of alternative remedies
- Excavation of shallow clayey soil in upper soil unit AOC planned for Summer 2018





---

## CONCLUSION: SVP MONITORING EFFECTIVE

- Monitoring fixed SVPs using low-purge equilibration method in low-permeability soil delivered consistent results
- Reliable soil vapor data successfully informed:
  - Risk characterization
    - Where to apply DPE
  - Remediation progress evaluation
    - Success in deeper soil
    - Lack of progress in shallow soil
  - Remediation decisions
    - Where an alternative remedy was required for shallow soil

---

# THANKS TO CO-AUTHORS



---

Dwight Harbaugh

Adam Ng

Dellilah Sabba

Janet Argyres



---

Michael Moes



---

# QUESTIONS?

Robert Plybon, P.E.

[bplybon@ekiconsult.com](mailto:bplybon@ekiconsult.com)

650-292-9100

eki

[www.ekiconsult.com](http://www.ekiconsult.com)

Burlingame, CA | Los Angeles, CA  
Oakland, CA | Centennial, CO

eki

**SLAC**  
NATIONAL ACCELERATOR LABORATORY