AEL environment presents

Bioremediation – Three Case Studies





Providing practical solutions for property investment and management property







INNOVATIVE LAND RESTORATION SOLUTIONS

Through Site Assessment & Remediation







My property requires remediation.

What are my options?




Potential Approaches

Many Options

Proper Design is Key


- Contact
- Reactivity
- Longevity






Potential Approaches

A Case for Well-Designed Bioremediation





McGuire et al, 2016



CASE STUDYTCE in Glaciolacustrine Environment



Background

GOAL:

Support Upcoming Sale of Property With Environmental Due Diligence


- Commercial/Industrial since 1970s
- Past and current waste generators
- TCE up to 50,000 μg/L
- Silt and sand sequences






Remediation

- EVO+KB1+ZVI
- Source zone + permeable reactive barrier
- Soil vapour extraction






- 98-99.5% reduction after pilot (6-months)
- 94-100% reduction after full-scale (3-Months)
- Vapour controlled by SVE and muted by source injection










- 98-99.5% reduction after pilot (6-months)
- 94-100% reduction after full-scale (3-Months)
- Vapour controlled by SVE and muted by source injection
- Site purchased based on preliminary results





CASE STUDY PCE in Bedrock



Background

GOAL:

Fulfill Post-Sale Agreement Including Remedial Intervention

- Industrial since 1900s
- Past waste generator
- PCE up to 2,100 μg/L
- Shallow channeled dolostone
- High permeability






Remediation


- High permeability
 - Single injection well (8")
 - Gravity feed injection

• EVO+KB1+FeS






- 12 Months Post-Injection
 - >99% PCE in source area
 - ~65% reduction of PCE plume







- 12 months post-injection
 - >99% PCE in source area
 - ~65% reduction of PCE plume
- 15 months post-injection
 - Rebound in deeper wells
 - Controlled by Risk Assessment













CASE STUDY TCE in Glacial Till




Background

GOAL:

Increase Property Value + Remove Potential Liability Via Environmental Due Diligence

- Commercial/industrial since 1950s
- Past waste generators
- TCE up to 200,000 μg/L
- Fine grained glacial till







Remediation

Source Zone Injection +
 Dual Phase Extraction

EVO+KB1+ZVI









Final Thoughts

- Invest in remedial design for success
- Bioremediation can address back diffusion
- **Combined remedies** often lead to a more successful remedial intervention
- Resist the temptation to walk away from problems
 - Quality information and advice can pay off with realistic solutions
 - Creative problem-solving can pay dividends down the line by **creating value**.





Questions?



Gavin Overbeeke - MESc, P.Geo D 905-978-1220 T 416-657-2367 goverbeeke@aelenv.com

Acknowledgements

Paul Dombrowski (Isotec)
Mathew Dotto (Isotec)
Winnie Lee (EcoMetrix)
Lara Alves Beese (EcoMetrix)
Paul Wilson (AEL)

Questions for later?
Call us at 1-800-267-4797

